

TWIN WELDING - EN 559 - Tlaková hadice pro technické plyny, kyslík, acetylen, 20 bar

Kód produktu: 10069
Tip



EN ISO 3821/EN 559

Lightweight, flexible twin hose for oxygen and acetylene, designed for use with mobile and stationary autogenous welding equipment. Dividing hoses allow hose expansion and collapse fitting to gas cylinder or welding gun. Also ideal for other purposes, e.g. air introduction on sandblasting equipment.
Normally installed using brass fittings, either with hose clamps or crimp-on fittings.
Please contact Gigan for further information.

Applications: Oxygen / Acetylene
Standard Length: 50 metres
Working Temperature: -20°C to 80°C
Inside Acc: EPDM Only: SBR/EPDM
Colour: Black
Reinforcement: Forster
Outside: EPDM
Colour: Red/Blue
Standards: EN ISO 3821/EN 559

Inside dia. [mm]	Outside dia. [mm]	Working Pressure BAR	Burst Pressure BAR	Bend Radius [mm]	Weight [kg/m]
4,0	12,0	20	60	40	113
5,0	14,0	20	60	50	153
6,0	16,0	20	60	63	193
8,0	20,0	20	60	100	282
10,0	25,0	20	60	150	390
15,0	38,0	20	60	200	595
20,0	50,0	20	60	300	810



EN ISO 3821/EN 559

Lightweight, flexible twin hose for oxygen and acetylene, designed for use with mobile and stationary autogenous welding equipment. Bending allows easy separation and simple fitting to gas cylinder or welding gun. Also ideal for other purposes, e.g. air replacement on sandblasting equipment. Normally installed using brass fittings, either with hose clamps or clamp-on fittings. Please contact Codan for further information.

Application: Oxygen / Acetylene
Standard Length: 50 metres
Working Temperature: -30°C to 80°C
Hose: Acc. 375M Dwg. 309/EPDM
Colour: Black
Reinforcement: 6 bar
Outside: EPDM
Colour: Red/Blue
Standards: EN ISO 3821/EN 559

Hose dia. (mm)	Outside dia. (mm)	Working Pressure BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (kg/m)
4,0	12,0	20	60	40	153
5,0	14,0	20	60	50	163
6,0	16,0	20	60	60	183
8,0	20,0	20	60	80	213
10,0	24,0	20	60	100	243

- Výrobce: [CODAN](#)
- Pracovní teplota: **-30°C až +70°C**
- Bezpečnost: **3 : 1**
- Materiál vnitřní: **SBR/NR**
- Materiál vnější: **NR/EPDM odolné otěru a ozónu**
- Výztuha: **Textilní opleť**
- Norma výrobku: **EN 559, UNI 4414, EN ISO 3821:2019**
- Médium: **technické plyny**
- Použití produktu: **technické plyny**
- Vnitřní barva: **černá**
- Vnější barva: **červená/modrá**
- Spirála: **Bez spirály**

Spojené hadice na dopravu kyslíku a acetylénu při svařování a dalších plynů, kromě (LPG, CNG a MPS). Hadice se standardně dodává v těchto kombinacích průměrů: 6+6, 8+8, 10+10, 6 (kyslík) + 8 (acetylen).

Varianty zboží

Objednací kód

Vnitřní rozměr

Vnější rozměr

Provozní tlak

Poloměr ohybu

Provedení

Hmotnost

Balení [MJ]

Mj

Vaše cena bez DPH

Sklad

606/013-SV020-03412

6 mm

13 mm

20 bar

40 mm

6,3+6,3 mm

0,35 kg

50

m

96,00 Kč

Lanškroun: **201,5**Pardubice: **3,0**Zlín: **84,0**Praha - Zličín: **0**Praha - Letňany: **0**Ostrava: **80,0**

606/013-SV020-03417

6 mm

13 mm

20 bar

40 mm

6,3+6,3 mm

0,35 kg

50

m

88,00 Kč

Lanškroun: **0**Pardubice: **0**Zlín: **0**Praha - Zličín: **0**Praha - Letňany: **0**Ostrava: **0**

608/015-SV020-03405

6 mm

15 mm

20 bar
40 mm
6,3 (K) +8 mm (A)
0,37 kg
40
m

96,00 Kč
Lanškroun: **85,3**Pardubice: **5,0**Zlín: **0**Praha - Zličín: **0**Praha - Letňany: **0**Ostrava: **0**
608/015-SV020-03412

6 mm
15 mm
20 bar
40 mm
6,3 (K) +8 mm (A)
0,37 kg
50
m

96,00 Kč
Lanškroun: **149,5**Pardubice: **0**Zlín: **0**Praha - Zličín: **0**Praha - Letňany: **0**Ostrava: **45,0**
808/015-SV020-03412

8 mm
15 mm
20 bar
40 mm
8+8 mm
0,38 kg
50
m

106,00 Kč
Lanškroun: **0**Pardubice: **0**Zlín: **0**Praha - Zličín: **0**Praha - Letňany: **0**Ostrava: **0**
609/015-SV020-03412

6 mm
16 mm
20 bar
60 mm
6,3 (K) +9 mm (A)
0,38 kg
50
m

112,00 Kč
Lanškroun: **80,6**Pardubice: **0**Zlín: **0**Praha - Zličín: **0**Praha - Letňany: **0**Ostrava: **0**
101/017-SV020-03412

10 mm
17 mm
20 bar
50 mm
10+10 mm
0,419 kg
50
m

137,00 Kč
Lanškroun: **20,0**Pardubice: **0**Zlín: **0**Praha - Zličín: **0**Praha - Letňany: **0**Ostrava: **0**