

DIN 24° FDLORX-45° - DKOL Female MegaCrimp koncovka, lehká řada, O-kroužek, 350 BAR

Kód produktu: 91112




91112



Female DIN 24° Cone Swivel

Bent Tube

- Light Series with O-Ring - 45°



Descr.	Prod. No.	Ø		H2	T		L	C	A1	
		mm	inch	mm	mm	inch	mm	mm	mm	
4G-8FDLORX45	7100-91852	1/4	6.4	M14x1.5	17.0	.64	16.2	62.5	36.5	8.0
4G-10FDLORX45	7100-92280	1/4	6.4	M16x1.5	18.0	.70	17.8	61.3	36.3	10.0
6G-10FDLORX45	7100-91895	5/16	7.9	M16x1.5	19.0	.67	17.1	63.4	39.3	10.0
6G-10FDLORX45	7100-92295	3/8	9.5	M16x1.5	19.0	.75	18.6	63.5	40.5	10.0
6G-12FDLORX45	7100-91975	3/8	9.5	M18x1.5	22.0	.74	18.9	64.0	40.9	12.0
6G-15FDLORX45	7100-92315	3/8	9.5	M20x1.5	27.0	.89	22.5	67.0	44.8	15.0
8G-15FDLORX45	7100-91935	1/2	12.7	M20x1.5	27.0	.79	20.2	79.0	47.1	15.0
10G-18FDLORX45	7100-91890	5/8	15.9	M20x1.5	32.0	.98	24.8	86.7	56.0	18.0
12G-20FDLORX45	7100-91975	3/4	19.1	M20x2.0	36.0	1.17	29.8	104.8	66.1	22.0
16G-28FDLORX45	7100-92325	1	25.4	M30x2.0	41.0	1.21	50.5	123.7	78.8	26.0
20G-32FDLORX45	7100-92335	1 1/8	31.8	M40x2.0	50.0	1.46	37.5	139.1	95.4	35.0

- Výrobce: [GATES](#)
- Pracovní teplota: **-40°C až +100°C**
- Materiál těsnění: **NBR o-kroužek**
- Materiál produktu: **Ocel (galvanicky potažená)**

Průměr nasazované hydraulické hadice je označen v tabulce písmenem D*.

Varianty zboží

Objednací kód

DN

Rozměr vněj. závitů

Šestihran

Provozní tlak

D,*

Zdvih

Série

Kóta A

Mj

Vaše cena bez DPH

Sklad

4G08FDLORX45

6 mm

M14x1,5 mm

19

350 bar

D=6 mm

T=16,2 mm

(L)

62,6

ks

288,00 KčLanškroun: **0**Pardubice: **0**Zlín: **0**Praha - Zličín: **0**Praha - Letňany: **0**Ostrava: **0**

5G10FDLORX45

8 mm

M16x1,5 mm

19

350 bar

D=8 mm

T=17,1 mm

(L)

67,1

ks

281,10 KčLanškroun: **0**Pardubice: **0**Zlín: **0**Praha - Zličín: **0**Praha - Letňany: **0**Ostrava: **0**

6G10FDLORX45

10 mm

M16x1,5 mm

19

350 bar

D=10 mm

T=18,6 mm

(L)

68,5

ks
349,60 Kč
Lanškroun: 0Pardubice: 0Zlín: 0Praha - Zličín: 0Praha - Letňany: 0Ostrava: 0
6G12FDLORX45
10 mm
M18x1,5 mm
22
350 bar
D=10 mm
T=18,9 mm
(L)
68,8
ks

288,00 Kč
Lanškroun: 0Pardubice: 0Zlín: 0Praha - Zličín: 0Praha - Letňany: 0Ostrava: 0
6G15FDLORX45
10 mm
M22x1,5 mm
27
350 bar
D=10 mm
T=22,5 mm
(L)
72,3
ks

404,60 Kč
Lanškroun: 0Pardubice: 0Zlín: 0Praha - Zličín: 0Praha - Letňany: 0Ostrava: 0
8G15FDLORX45
12 mm
M18x1,5 mm
27
350 bar
D=12 mm
T=29,7 mm
(L)
92,9
ks

432,00 Kč
Lanškroun: 0Pardubice: 0Zlín: 0Praha - Zličín: 0Praha - Letňany: 0Ostrava: 0
8G18FDLORX45
12 mm
M26x1,5 mm
32
350 bar
D=12 mm
T=26,9 mm
(L)
94,9
ks

468,30 Kč
Lanškroun: 0Pardubice: 0Zlín: 0Praha - Zličín: 0Praha - Letňany: 0Ostrava: 0