


HYDRAULICKÝ ZÁMEK DVOJČINNÝ - 325.5121.000 VRDE/CIL 38 DO 300 BAR


Kód produktu: **70130**

Novinka


70130




70130



70130



70130






70130

DOUBLE PILOT CHECK VALVE
CYLINDER STUD MOUNTING

325.5121.000

WPC series are used to lock an actuator and make it insensitive to external forces.
The passage of the fluid is via a command pilot. Max pressure: 350 bar.
They are particularly suitable for mounting on hydraulic cylinders
when the space between the mounts is limited.

SCHEMA IDRAULICO
HYDRAULIC DIAGRAM

TIPO/TYPE	A	B	C	D	E	F	G	L
WPC/GC 38	3/8	40x30	80	84,5	13	20	16,5	110,5

70130



- Výrobce: [PIOTTI](#)
- Pracovní teplota: **-20°C až +80°C**
- Médium: **Olej**
- Materiál produktu: **Lakovaná ocel**

Varianty zboží

Objednací kód

Vnitřní závit

Provozní tlak

Série

Ovládání

Hmotnost

Mj

Vaše cena bez DPH

Sklad

325.5121.000

3x 3/8"

300 bar

325.5121

dvojčinný

2,5 kg

ks

1 158,50 KčLanškroun: **2,0**Pardubice: **0**Zlín: **0**Praha - Zličín: **0**Praha - Letňany: **0**Ostrava: **0**