

AL-D PNEUMATICKÝ LUBRIKÁTOR VZDUCHU - Maznice vzduchu, řada AL-20 až 60 D

Kód produktu: 74003



AL-D



AL-D



AL-D

Lubricator

AL20-D to AL60-D

AL30-D

How to Order

30 - 03 B - D

① ② ③ ④

Basic standard Symbol Selection

Select one each for ① to ④
 When basic form specification is required, indicate in alphanumeric code.
 Examples: AL30-D, [AL30-D](#)

	Symbol	Description	Port size			
			20	30	40	60
Pipe thread type	—	—	●	●	●	●
	1/2	1/2	—	—	—	—
	3/4	3/4	—	—	—	—
	1	1	—	—	—	—
	1 1/2	1 1/2	—	—	—	—
	2	2	—	—	—	—
	3	3	—	—	—	—
	4	4	—	—	—	—
	5	5	—	—	—	—
	6	6	—	—	—	—
Port size	1/2	1/2	—	—	—	—
	3/4	3/4	—	—	—	—
	1	1	—	—	—	—
	1 1/2	1 1/2	—	—	—	—
	2	2	—	—	—	—
	3	3	—	—	—	—
	4	4	—	—	—	—
	5	5	—	—	—	—
	6	6	—	—	—	—
	7	7	—	—	—	—
Option (Mounting)						
①	B	—	—	—	—	—
		Without mounting system	—	—	—	—
		With bracket	—	—	—	—
		With bracket and drain plug	—	—	—	—
		With drain plug	—	—	—	—
		With drain plug and drain hose	—	—	—	—
		With drain plug and drain hose and drain plug	—	—	—	—
		With drain plug and drain hose and drain plug and drain hose	—	—	—	—
		With drain plug and drain hose and drain plug and drain hose and drain plug	—	—	—	—
		With drain plug and drain hose and drain plug and drain hose and drain plug and drain hose	—	—	—	—
②	B	—	—	—	—	—
		Flow direction: Left to right	—	—	—	—
		Flow direction: Right to left	—	—	—	—
		Flow direction: Left to right and Right to left	—	—	—	—
		Flow direction: Right to left and Left to right	—	—	—	—
		Flow direction: Left to right and Right to left and Right to left and Left to right	—	—	—	—
		Flow direction: Right to left and Left to right and Left to right and Right to left	—	—	—	—
		Flow direction: Left to right and Right to left and Right to left and Left to right and Left to right and Right to left	—	—	—	—
		Flow direction: Right to left and Left to right and Left to right and Right to left and Right to left and Left to right	—	—	—	—
		Flow direction: Left to right and Right to left and Right to left and Left to right and Left to right and Right to left and Right to left and Left to right	—	—	—	—
③	B	—	—	—	—	—
		Without drain hose	—	—	—	—
		With drain hose	—	—	—	—
		With drain hose and drain plug	—	—	—	—
		With drain hose and drain plug and drain hose	—	—	—	—
		With drain hose and drain plug and drain hose and drain plug	—	—	—	—
		With drain hose and drain plug and drain hose and drain plug and drain hose	—	—	—	—
		With drain hose and drain plug and drain hose and drain plug and drain hose and drain plug	—	—	—	—
		With drain hose and drain plug and drain hose and drain plug and drain hose and drain plug and drain hose	—	—	—	—
		With drain hose and drain plug and drain hose and drain plug and drain hose and drain plug and drain hose and drain plug	—	—	—	—
④	B	—	—	—	—	—
		Flow direction: Left to right	—	—	—	—
		Flow direction: Right to left	—	—	—	—
		Flow direction: Left to right and Right to left	—	—	—	—
		Flow direction: Right to left and Left to right	—	—	—	—
		Flow direction: Left to right and Right to left and Right to left and Left to right	—	—	—	—
		Flow direction: Right to left and Left to right and Left to right and Right to left	—	—	—	—
		Flow direction: Left to right and Right to left and Right to left and Left to right and Left to right and Right to left	—	—	—	—
		Flow direction: Right to left and Left to right and Left to right and Right to left and Right to left and Left to right	—	—	—	—
		Flow direction: Left to right and Right to left and Right to left and Left to right and Left to right and Right to left and Right to left and Left to right	—	—	—	—
⑤	B	—	—	—	—	—
		Unit	—	—	—	—
		Unit	—	—	—	—
		Unit	—	—	—	—
		Unit	—	—	—	—
		Unit	—	—	—	—
		Unit	—	—	—	—
		Unit	—	—	—	—
		Unit	—	—	—	—
		Unit	—	—	—	—

- Výrobce: [SMC](#)
- Materiál produktu: **POM**
- Médium: **Vzduch, neutrální plyny, neutrální média**
- Pracovní teplota: **-5°C až 60°C**
- Použití produktu: **Úprava tlaku vzduchu**

Slouží k přimazávání prvků pracujících se stlačeným vzduchem. Doporučený olej: turbínový ISO VG32. Výhody: přesné nastavení četnosti mazání podle stupnice. Průhledný ochranný kryt jímek umožňuje lepší viditelnost a bezpečnost. Při instalaci této řady AL-D by měl být nainstalován zpětný ventil k ochraně předřazených prvků.

Varianty zboží

Objednací kód

Provozní tlak
Regulace
Vnitřní závit
Hmotnost
Série
Mj
Vaše cena bez DPH

Sklad
SMC-AL20-F02-D

10 bar
4.000 l/min.
G 1/4"
0,102 kg
20AL-D
ks

1 053,10 Kč

Lanškroun: 0Pardubice: 0Zlín: 0Praha - Zličín: 0Praha - Letňany: 0Ostrava: 0

SMC-AL30-F02-D

10 bar
6.000 l/min.
G 1/4"
0,192 kg
30AL-D
ks

1 355,10 Kč

Lanškroun: 0Pardubice: 0Zlín: 0Praha - Zličín: 0Praha - Letňany: 0Ostrava: 0

SMC-AL30-F03-D

10 bar
6.000 l/min.
G 3/8"
0,186 kg
30AL-D
ks

1 355,10 Kč

Lanškroun: 0Pardubice: 0Zlín: 0Praha - Zličín: 0Praha - Letňany: 0Ostrava: 0

SMC-AL40-F02-D

10 bar
8.000 l/min.
G 1/4"
0,399 kg
40AL-D
ks

1 549,30 Kč

Lanškroun: 0Pardubice: 0Zlín: 0Praha - Zličín: 0Praha - Letňany: 0Ostrava: 0

SMC-AL40-F04-D

10 bar
8.000 l/min.
G 1/2"
0,379 kg
40AL-D
ks

1 549,30 Kč

Lanškroun: 0Pardubice: 0Zlín: 0Praha - Zličín: 0Praha - Letňany: 0Ostrava: 0

SMC-AL40-F04-R-D

10 bar
8.000 l/min.
G 1/2"
0,38 kg
50AL-D
ks

1 549,30 Kč

Lanškroun: 0Pardubice: 0Zlín: 0Praha - Zličín: 0Praha - Letňany: 0Ostrava: 0

SMC-AL50-F06-D

10 bar
17.700 l/min.
G 3/4"
0,984 kg
50AL-D
ks

1 801,00 Kč

Lanškroun: 0Pardubice: 0Zlín: 0Praha - Zličín: 0Praha - Letňany: 0Ostrava: 0

SMC-AL60-F10-D

10 bar

17.050 l/min.

G 1"

1,1 kg

60AL-D

ks

2 200,00 Kč

Lanškroun: 0Pardubice: 0Zlín: 0Praha - Zličín: 0Praha - Letňany: 0Ostrava: 0